

EVANCE ISKRA R9000 ADVANCED SMALL WIND TURBINE



Renewable energy is key to our low-carbon future, as well as diversifying our energy sources.

Today wind power continues to gain ground as a profitable and effective energy source.

Evanco is at the heart of this energy revolution, supporting homeowners, businesses and organisations around the world, to become independent green energy producers and reduce their bills.

Evanco is an accredited MCS installer, and factory process control and products are MCS compliant.

The Evance Iskra R9000 is eligible for Feed-in Tariffs.

The Evance Iskra R9000 small wind turbine is the result of years of dedicated research and development, and is based on engineering experience of designing big wind turbines.

Specifically designed to capture more energy at lower wind speeds makes the R9000 the most efficient 5kW turbine available.

The R9000 has a patented high-efficiency generator which converts up to 96% of the energy captured into electricity in on and off grid applications.

Combining our patented state-of-the-art technology and elegant design, the R9000 belongs to the 'next generation' of small wind turbines, offering class leading quality, performance and reliability.

Performance - class leading energy yield

Efficiency - up to 96% of energy captured is converted into electricity

Reliability - existing installations average >99% up time

Quiet operation - advanced blade design & direct drive/no gearbox

Durability - conforms to IEC 61400-2 international standard


Safety - two automatic & independent over speed protection systems

The Evance Iskra R9000, the industry's most reliable and efficient turbine, helping to generate free clean energy for schools, farms, rural homes & light commercial sites.

SPECIFICATIONS

Architecture	Upwind, 3 bladed rotor, self regulating
Rated Power	5kW @12m/s (26.8mph), continuous to 60m/s (134mph)
Annual Energy Yield	8780kWh with Annual Mean Wind Speed (AMWS) of 5m/s (11mph) (to IEC & BWEA Standards)
Cut-In Wind Speed	3m/s (6.7mph)
Cut-Out Wind Speed	None. Continuous generation to survival wind speed
Survival Wind Speed	60m/s (134mph)
IEC Turbine Class	Conforms to IEC 61400 to Class II - AMWS up to 8.5m/s (19mph)
Control System	Patented Reactive Pitch™ control
Rotor Diameter	5.5m (17.7')
Rotor Speed	200rpm nominal, 230rpm maximum
Blade Type	Fully optimised aerofoil ensuring maximum yield & minimum noise
Blade Material	Glass fibre reinforced composite, low reflection, UV & anti-erosion coatings
Generator	Patented brushless direct drive, air-cored high efficiency Permanent Magnet Alternator
Gearbox	None required (see generator)
Emergency Braking	Patented automatic ElectroBrake™ (with manual control for servicing). No moving parts.
Yaw Control	Passive tail vane and rotor
Tower Height	10m, 12m, 15m & 18m (33', 40', 50', 60' & US only 80')
Tower Types	Free-standing (monopole), hydraulic RAM & Gin pole tilt
Tower Foundation	Root & pad options
Tower Top Mass	325kg (715lbs) complete (excl tower)
Design Longevity	20 years minimum. Annual service inspection
Noise	Lp,60m = 45dB(A). BWEA Reference Sound Level at 8m/s & 60m distance
Warranty	5 years (see Evance Terms & Conditions for details)

Average Power vs. Wind Power



EVANCE

Unit 6
Weldon Road
Derby Road Industrial Estate
Loughborough
Leicestershire LE11 5RN
United Kingdom

T: +44 (0)1509 215669
F: +44 (0)1509 267722
E: enquiries@evancewind.com
www.evancewind.com

We are continually improving our products and reserve the right to alter the above specifications at any time without notice. All trademarks and registered trademarks used herein are the property of their respective owners.